

TOOLBOX TALK – 41

Use of Defective Vehicle Steering Wheel Covers

Starting up or moving buses in the course of repair activities could prove fatal.

The use of defective vehicle steering wheel covers in the course of bus repairs is absolutely essential to prevent vehicles being moved or started up.

A defective vehicle steering wheel cover is put in place over the steering wheel to make it obvious that the bus **MUST NOT** be started up or moved.

Its use shall be standard across all garages, and will be rigorously enforced.

Each operative should have a personal cover marked with their name or have a card which can be inserted into a pouch.

They must also be used for repairs during run out.

Remember

- 🚌 Before work starts on any vehicle place the cover over the steering wheel
- 🚌 If anyone else is working on the vehicle **DO NOT UNDERTAKE WORK ACTIVITIES OR START THE VEHICLE** without communicating this to the them first
- 🚌 When the work has been completed the cover must be removed from the steering wheel
- 🚌 The steering wheel cover must not be used for any other purpose
- 🚌 It must be used for all inspection, servicing and repair of vehicles



TOOLBOX TALK – 41

Use of Defective Vehicle Steering Wheel Covers

I acknowledge that I must always use a defective vehicle steering wheel cover on any bus I am inspecting, servicing or repairing, including during morning run out.

I understand I must not turn on the ignition of any bus where a steering wheel cover is fitted.

Employee to complete in block capitals

NAME: NUMBER:

DEPOT:

JOB TITLE:

SIGN: DATE:

Copy to File